

Circular


PA600M

By BENITO © ®

60L



BLOQUEO DE SEGURIDAD
BUTTOR DE SÉCURITÉ
SECURITY LOCKING SYSTEM
BLOQUEIO DE SEGURANÇA



Opcional | En option | Optional



*VC4GR



*KIT

PIES REFORZADOS
PIEDS REFORCÉES
REINFORCED GUSSET PLATES
PÉS REFORÇADOS



Variantes | Variantes | Alternatives



PA600MI





PA616M



PA616I

Vaciado | Vidage | Emptying



Ref.		A	Ø B	H	H1
PA600M	60L.	465 mm	375 mm	885 mm	525 mm
PA600MI	60L.	465 mm	375 mm	885 mm	525 mm



Cubeta abatible de acero con agujeros triangulares con tratamiento Ferrus, proceso protector del hierro, que garantiza una óptima resistencia a la corrosión. Imprimación epoxi y pintura poliéster en polvo color gris RAL 7011 (PA600M). Cubeta apoyada en estructura de tubo de Ø40 mm con base de anclaje y pletinas rectangulares con dos agujeros de Ø12 mm para su fijación en el suelo. Anclaje recomendado: Mediante cuatro pernos de expansión de M8. Opcional: Acero inoxidable pulido brillante (PA600MI).

Corbeille basculante en acier perforé à motifs triangulaires traité avec Ferrus, un procédé qui protège le fer et garantit une résistance optimale à la corrosion. Couche primaire époxy et peinture poudre polyester de couleur gris RAL 7011 (PA600M). Corbeille qui repose sur une structure en tube de Ø 40 mm avec base d'ancrage et plats rectangulaires munis de deux trous de Ø 12 mm pour être fixée au sol. Ancrage recommandé : Par quatre boulons à expansion M8. En option : Acier inoxydable poli brillant (PA600MI).

Stainless steel tipping bin with triangular holes, treated with Ferrus, a protective process for iron that guarantees high resistance to corrosion. Epoxy primer and grey RAL 7011 polyester powder coating paint (PA600M). Bin supported on a Ø40 mm tube structure with an anchor base and rectangular bars with two Ø12 mm holes for fixing to the ground. Recommended anchoring: Four M8 expansion bolts. Optional: Shiny, polished stainless steel (PA600MI).

