

Basculante

PA623P



30L



Variantes / Variantes / Alternatives / Variações




PA623




PA623S



PA623D



Ref.		A	Ø B	H	H1
PA623	30L.	400 mm	320 mm	1465 mm	460 mm
PA623D	2x32L	738 mm	320 mm	1465 mm	460 mm
PA623S	30L.	400 mm	320 mm	1465 mm	460 mm
PA623P	30L	410 mm	320 mm	750 mm	460 mm



Vaciado / vidage / Emptying / Despejo



CARACTERÍSTICAS | CARACTERISTIQUES | CHARACTERISTICS

Material: Cubeta cilíndrica en plancha embutida. Perfil en plancha de acero de 75 mm para fijar la cubeta y anclar a la pared.

Acabados: Zincado electrolítico por inmersión, aplicando una posterior capa en color negro forja.

Matériau: Corbeille murale basculante cylindrique en tôle d'acier emboutie ouvragée, Ø60 mm.

Finition: Électro-zingage+après polyester zinc + Thermolaquage polyester oxyron noir de forge.

Scellement recommandé: spitage.

Material: Cylindrical bin made steel. 75 mm steel lateral support to fix the bin and anchor the element to the wall.

Finish: Electrolyte zinc plating undercoat plus forged black oxiron coat.

VACIADO | VIDAGE | EMPTYING

EXTRACCIÓN | EXTRACTION | REMOVING

ANCLAJE | SCELLEMENT | ANCHORAGE

