

BENITO -Urban

Barcino

UM3031




Variantes | Variantes | Alternatives



UM305S

UM302

| Ref. | A | B | H | H1 |
|--------|---------|--------|--------|--------|
| UM3031 | 1800 mm | 700 mm | 785 mm | 440 mm |
| UM305S | 540 mm | 700 mm | 785 mm | 440 mm |
| UM302 | 540 mm | 700 mm | 785 mm | 440 mm |



Pies de fundición dúctil con acabado imprimación epoxi y pintura poliéster en polvo color negro forja. Tablones de sección 40 x 35 mm de madera tropical tratada con Lignus, protector fungicida, insecticida e hidrófugo. Acabado color caoba. Tornillos de acero inoxidable. Anclaje recomendado: Tornillos de fijación al suelo de M10 según superficie y proyecto. Opcional: Se puede suministrar madera con certificado FSC o PEFC.

Piètement en fonte ductile avec finition couche primaire époxy et thermolaquage polyester noir de forge. Lattes de bois tropical de section 40 x 35 mm traité avec Lignus protecteur fongicide, insecticide et hydrofuge. Finition teinte acajou. Vis en acier inoxydable. Ancrage recommandé : vis M10 pour la fixation au sol, en fonction de la surface et du projet. En option : bois certifié FSC ou PEFC.

Ductile iron legs with epoxy primer coating and black wrought iron coloured polyester powder coated finish. Tropical wood boards measuring 40 x 35 mm, treated with Lignus, a fungicide, insecticide and waterproofing agent. Mahogany colour finish. Stainless steel bolts. Recommended anchoring: M10 bolts to anchor to the ground, depending on the surface and the project. Optional: FSC- or PEFC-certified wood can be supplied.

